

# SPH 3-6K & SPH3-6KTL BL-UP

- Smart load management via dry contact(SPH TL BL-UP)
- UPS function, 10ms transition(SPH TL BL-UP)
- Scalable system configuration(SPH TL BL-UP)
- VPP interface ready
- Remote smart O&M
- 1.5 DC/AC Ratio



P O W E R  
- I N G O  
T O M O -  
R R O W O

**G**ROWATT

[www.ginverter.com](http://www.ginverter.com)

Datasheet	SPH3000&SPH3000 TLBL-UP	SPH3600&SPH3600 TLBL-UP	SPH4000&SPH4000 TLBL-UP	SPH4600&SPH4600 TLBL-UP	SPH5000&SPH5000 TLBL-UP	SPH6000&SPH6000 TLBL-UP
<b>Input data(PV)</b>						
Max. recommended PV power (for module STC)	6000W	7200W	7600W	8200W	8600W	9000W
Max. DC voltage	550V					
Start voltage	120V					
MPP voltage range	120-550V/360V					
No. of MPP trackers	2					
No. of PV strings per MPP tracker	1					
Max. input current per MPP tracker	13.5A					
Max. short-circuit current per MPP tracker	16.5A					
<b>Output data(AC)</b>						
AC nominal power	3000W	3600W	4000W	4600W	5000W	6000W
Rated Apparent Power	3000VA	3000VA	4000VA	4600VA	5000VA	6000VA
Nominal AC voltage (range)	230V/ (180Vac-270Vac)					
AC grid frequency (range)	50Hz/60Hz (45Hz-55Hz/55Hz-65Hz)					
Rated input/output current	13.5/13.5A&13.5/13.5A	13.5/16A&16/16A	13.5/17.5A&17.5/17.5A	13.5/20A&20/20A	13.5/22A&22A/22A	13.5/27A&27/27A
Adjustable power factor	0.8leading...0.8lagging					
THDI	<3%					
AC grid connection type	Single phase					
<b>Battery data (DC)</b>						
Battery voltage range	42~59V					
Max charging and discharging current	66A	75A	85A	85A	85A	85A
Continuous charging and discharging power	3000W	3600W	4000W	4000W	4000W	4000W
Type of battery	Lithium /Lead-acid					
<b>Backup power(AC)</b>						
Rated Apparent Power	3000VA&3000VA	3000VA&3680VA	3000VA&4000VA	3000VA&4000VA	3000VA&4000VA	3000VA&4000VA
Rated output current	13A/13A	13A/16A	13A/17.5A	13A/17.5A	13A/17.5A	13A/17.5A
Nominal AC output voltage	230Vac					
Nominal AC output frequency	50/60HZ					
THDv	<3%					
Switch time(SPH TL BL-UP)	<10ms					
<b>Efficiency</b>						
MAX. efficiency	97.20%	97.20%	97.30%	97.40%	97.50%	97.60%
European efficiency	97%	97%	97.10%	97.10%	97.20%	97.20%
MPPT efficiency	≥99.5%					
<b>Protection devices</b>						
DC switch	Yes					
DC reverse polarity protection	Yes					
AC/DC surge protection	Yes					
Battery reverse protection	Yes					
AC short-circuit protection	Yes					
Ground fault monitoring	Yes					
Grid monitoring	Yes					
Anti-islanding protection	Yes					
Residual-current monitoring unit	Yes					
Insulation resistance monitoring	Yes					
<b>General data</b>						
Dimensions (W / H / D)	461/565/188mm					
Weight	27kg					
Operating temperature range	-25°C ... +60°C					
Nighttime power consumption	< 10 W					
Topology	Transformerless					
Cooling	Natural					
Protection degree	IP65					
Relative humidity	0~100%					
Altitude	2000m					
Battery DC connection.	OT Terminal					
AC connection	Connector					
Display	LCD+LED					
Interfaces:RS485/CAN/USB	Yes					
Monitor : RF/WIFI/GPRS	Optional					
Country of Manufacture	China					

CE, IEC62109, G98/G99, VDE0126-1-1, AS4777, CEI 0-21, VDE-AR-N4105, UTE C 15-712, EN50549, IEC 61727, IEC 62116, IEC 62040, C10/11, NRS 097-2-1